

MG ORGANICS PVT.LTD.

(Manufacturers of Speciality Chemicals & Thinners)

HD-24, UPSIDC INDL. AREA,
SIKANDRABAD , BSR , UP-203205

Tel: 0120-6544000 , 09718579800, 09818579800

e-mail : mgopl@rediffmail.com

www.mgorganics.com

Technical Data

***PAIN*T STRIPPER XM-99 (Solvent Base Heavy Duty Paint Remover)**

Product description

PAINT STRIPPER XM-99 is a liquid solvent base viscous paint stripper which is specially formulated to remove all types of paint coatings from the ferrous metal surface.

BENEFITS:

- Rapidly removes chemically resistant coatings, such as polyurethanes and epoxy.
- Effectively removes epoxy base coats and zinc chromate primers along with the topcoat.
- Thixotropic - clings to inclined, vertical and overhead surfaces.
- Safe on common structural metals, including aluminum, magnesium, stainless steel, mild steel , high strength steel, copper and zinc.



Product Specifications

Colour	Light Brown Colour Liquid
Chemical Composition	Mixture of Chlorinated solvents and additives
Odour	Sweet
Foaming Tendency	Nil
Reliability	Good
Handling	Avoid skin contact
Solubility	Good
Toxicity	Moderate
Flash Point	Nil
Pollution Hazard	Moderate

HOW TO USE

Put **PAINTE STRIPPER XM-99** as supplied (concentration) to the processing tank. Dip the components in *PAINTE STRIPPER XM-99* tank at a room temperature till the coating is completely removed. Tank out the components and rinse with jet of eater to flush off any residual film or coating. Normally the dipping time is about 5 to 10 minutes depending upon the type and number of coatings to be stripped off. Or apply by brush on scratched surface of old paint.

Product Application Equipment: Poly plastic Tank

Chemical Replenishment

Discard the bath when its paint removing action slows and make it fresh.